



Eno omrežje, ena varnost, ena IT izkušnja

26. September 2023, Marko Kašić, Vodilni ICT inženir

A1 ICT Distribucija



- Ekipa ustanovljena **2004**
- **Širok portfelj** varnostnih rešitev
 - Endpoint Security
 - Network Security
 - EDR in NDR
 - Privileged Access Management
 - Email Security
 - Secure Data Backup
 - Log management in SIEM
 - Omrežne rešitve (stikala, wifi, ...)
 - Dodatna oprema za računalnike
 - ...
- **Izkušena** ekipa



STORMSHIELD



Cambium Networks™

ENERGY
LOGSERVER



VECTRA
SECURITY THAT THINKS.®

COMMScope®
RUCKUS®



censornet.




Gartner Survey Shows 75% of Organizations Are Pursuing Security Vendor Consolidation in 2022

- ***Sixty-five percent of organizations consolidate to improve risk posture.***
- ***Only 29% of organizations consolidate to reduce spending on licensing.***
- ***SASE and XDR are opportunities for consolidation: 41.5% of organizations plan to have adopted SASE by the end of 2022.***

Konsolidacija omrežja


- Hitrejša zasnova in načrtovanje omrežja
- Hitrejša implementacija zaradi boljše kompatibilnosti oz. integracije orodij med seboj
- Homogeno omrežje je enostavneje vzdrževati (hitrejša odprava napak)
- Management homogenega omrežja omogoča pogled skozi en portal





Eno omrežje

Eno omrežje, ena varnost, ena IT izkušnja



Osredotočite se na posel, ne na omrežje

ENA
izkušnja



Operativna
odličnost



Predvidljivi
rezultati



Ena izkušnja



APIs

Cloud Management & Analytics

- Planning
- Deployment
- Operations



Integrated Network Security

Indoor LAN



Wi-Fi



Switching



Security &
SD-WAN

Outdoor Campus



Outdoor Wi-Fi,
60GHz Backhaul,
Ruggedized Switching

Eno omrežje





Brezžične dostopne točke
cnPilot WiFi5 in XV / XE WiFi 6 / 6E

Cambium Networks WiFi

- cnPilot Indoor



	E425	E410
Radios	Dual band 2x2	Dual band 2x2
Wi-Fi	11ac.wave2	11ac.wave2
5GHz EIRP	25dBm	30.5dBm
Ethernet	3 x GE PoE out	1 x GE
BLE	No	No
Environment	Wall plate	Indoor
Key Value	Flexible mounting USB port	Cost effective 2x2

- cnPilot Outdoor



	E510	E700
Radios	2x2:2	4x4:4
Wi-Fi	11ac wave2	11ac wave2
Capacity	1.3 Gbps	2.13 Gbps
Antenna	Integrated 8 dBi omni	Integrated 8 dBi omni
Clients	256	512
Transmit power	28 dBm	28 dBm
Ethernet	1 x GE	1 x GE 1 x GE PoE-Out
Temperature range	-40° to +65°C	-40° to +65°C

Cambium Networks WiFi 6 / 6E







	XV2-21X	XE3-4
Radios	Dual Band 2x2	Tri-Band, Tri-Radio 4x4/2x2
Wi-Fi	Wi-Fi 6	Wi-Fi 6/6E
5GHz EIRP	33 dBm	30dBm
Uplinks	1 x GbE	1 x GbE, 1 x 2.5GbE
BLE	✓	✓



	XV2-23T
Radios	2
Bands	5GHz: 2x2 2.4GHz: 2x2
Wi-Fi	802.11ax
5GHz EIRP	27 dBm
Ethernet	Gigabit PoE-In
Antenna	10 dBi

Cambium Networks zunanji AP


XV2-2T WiFi6




Test dosega s pametnim telefonom




XV2-2T



0m – 940Mbps



450m – 127Mbps



1km – 40Mbps

*Na konkurenčne AP-je se ni
bilo več možno povezati pri tej razdalji*

Povečane potrebe pri uporabi omrežja

Video



AR/VR



Cloud



Sledenje



Internet of Things



4K/8K Video



Software Defined radio

Dvakrat 4x4 5GHz ali enkrat 8x8



Dvojna kapaciteta omrežja, za visoko gostoto uporabnikov
Povišana MU-MIMO kapaciteta za najbolj razširjene kliente 11ac

Idealno za okolja z mešanimi napravami tipa 11n, 11ac ter 11ax


Povečana kapaciteta omrežja, nižja latenca

MU-OFDMA, MU-MIMO, IOT ready

Idealno kadar je omrežje vsaj 50% 11ax and 11ax IOT naprav

Primer uporabe

500 seat auditorium
400+ simultaneous devices
95%+ 5GHz




**2-radio
AP Design**

12 APs

14 radios used

10 2.4GHz radios **turned off**



**5-radio
AP Design**

4 High Density APs

20 radios used

1 2.4GHz radio turned off

The logo consists of a large, 3D red letter 'A' followed by a white number '1'. The background is a dark blue, out-of-focus image of a circuit board with glowing blue light points and a transparent, glowing square frame on the right side.

A1

Stikala L2 in L3
cnMatrix

Cambium Networks stikala L2 / L3



cnMaestro



Profesionalna stikala s funkcionalnostmi na L2 in L3

Avtomatizacija pravilnikov
Profiliranje naprav in samodejna konfiguracija

Upravljanje preko cnMaestro cloud ali on-premise
Neprekinjeno delovanje tudi brez povezave do managementa

Možnost samodejnega brisanja konfiguracije v primeru odtujitve
naprav ali varnostnega incidenta

Najboljši v razredu v TCO

Cambium Networks serija TX-2K

Ojačana stikala



- 8-port, 16-port, 24-port
- PoE & Passive PoE, High Power PoE (90w)
- Dvojno napajanje s hitro menjavo
- Cambium (GPS) Sync – redundančna vira
- Ojačana oprema s širokim temperaturnim obsegom delovanja:
-10°C up to 65°C

The logo consists of a large, 3D red letter 'A' followed by a smaller, white number '1'. The background is a dark blue, out-of-focus image of a circuit board with glowing blue light points and a transparent, glowing cube-like structure.

Point-to-Point in Point-to-Multipoint
ePMP in 60GHz

Cambium Networks ePMP



4X4 MU-MIMO sector antenna

70° beam width
4 x RP-SMA connectors
17 dBi gain
Dual polarization
IP65
-40 °C to +60 °C



4X4 dual horn MU-MIMO antenna

60° beam width
4 x RP-SMA connectors
12 dBi gain
IP55
-40 °C to +60 °C



2x2 sector antenna MIMO

120° beam width
2 x RP-SMA connectors
18 dBi gain
IP65
-40 °C to +60 °C



2x2 MIMO beamforming antenna


uplink only
90° beam width
2 x RP-SMA connectors
17 dBi gain
IP65
-30 °C to +55 °C

Point to Point

do 64km


64 km

64 km



Point to Multipoint

Povezovanje domačih ali poslovnih uporabnikov



Cambium Networks ePMP



Cambium Networks cnWave 60GHz

Distribution Node



V5000
Dual Sector

Client Nodes (PMP or PTP)



V3000
High Gain
44.5 dBi Dish



40.5 dBi Dish



V2000
Flexible
Mid-Range



V1000
Small
Form-Factor




Network Service Edge
NSE

Cambium Networks Network Service Edge (NSE)



WAN EDGE



- Routing
- WAN Load-Balancing and failover
- Bandwidth Control
- WAN QoS
- SD-WAN

SECURITY




- Firewall
- **IoT Security**
- VPN with MFA
- **LAN security assessment**
- **Zero Trust Network Access (ZTNA)**
- IDS / IPS

NETWORK SERVICES





- DHCP
- RADIUS
- **Directory connectors**

Synthesize sensors across Wi-Fi, Wired ports and WAN
Qualify service across the enterprise network
Clear the blind spot in IoT security



NSE 3000 Edge Appliance


Cambium Networks NSE Threats



Cambium Networks NSE Vulnerabilities

DashboardNotificationsConfigurationSecurityDetailsPerformanceSoftware UpdateToolsClients

ThreatsVulnerabilitiesVPN



Vulnerability Blocked

300 Blocked

Last 24 Hours

Critical

120

Major

120

Minor

80

Clients

34

Top Vulnerability

HTTP Port Open

Clients

Search

IP Address	Hostname	Device Type	Device OS	Last Scan	Total	Vulnerabilities	Severity
192.168.231.111	Harry	Phone	Android	4 days ago	91/53		
192.168.1.1	Job	Laptop	Window	55 days ago	35/75		
192.168.231.101	Richard	Laptop	Window	54 seconds ago	21/56		
192.168.100.206	Mei	Phone	Android	19 minutes ago	82/72		
192.168.100.209	Birney	Phone	Android	28 seconds ago	28/31		
192.168.231.103	Ian	Laptop	Window	18 days ago	49/41		

All Vulnerabilities

Search

Severity	Vulnerability	Devices Impacted	Percentage
Critical	Unpatched Windows OS	91/53	
Critical	HTTP Port Open	35/75	
Critical	Port 80 Open	21/56	
Label	Port 80 Open	82/72	
Critical	Port 2080 Open	28/31	
Major	Port 70 Open	49/41	5%

Unpatched Windows OS

Search

IP Address	MAC Address	Status	Device OS	Device Model	Updated	Vulnerabilities
192.168.100.207	AA:B2:CC:33:DD:21:DF	Offline	iOS	iPhone	1 hour ago	31
192.168.1.3	AA:B9:CC:54:DD:42:DF	Online	Windows	Lenovo	43 days ago	0
192.168.100.202	AA:BB:CC:33:DD:AD:DF	Online	Android	Samsung S1	4 days ago	27
192.168.231.109	AA:BB:C6:33:DD:21:DF	Offline	Linux	iPhone	38 days ago	20
192.168.231.105	AA:BB:5C:33:DD:21:DF	Online	Android	Samsung S1	41 seconds ago	0
192.168.100.205	BA:BB:9C:90:DD:21:DF	Online	Windows	iPhone	1 second ago	79
192.168.100.203	BA:BB:CC:33:DD:44:DC	Offline	iOS	Lenovo	36 hours ago	0
192.168.231.114	AA:BB:CC:33:DD:AD:DF	Online	Windows	Samsung S1	8 minutes ago	62



Upravljanje
cnMaestro in cnMaestro X

Cambium Networks cnMaestro management



cnMaestro
Cloud controller



cnMaestro
Image for virtualization



Wi-Fi Designer Planning Tool





- Online orodje postavitve za Cambium Enterprise WiFi
- Enostavno za uporabo
- Brezplačno
- Ustvarite seznam opreme za implementacijo




Cambium LinkPlanner

- LINKPlanner omogoča pregled scenarijev „kaj če“ – ti bazirajo na geografiji: razdalja, višina oddajnikov, moč oddajanja in ostali faktorji vplivajo na učinkovitost povezave.



LinkPlanner Cloud




<https://lp.cambiumnetworks.com>

A1

DEMO

Eno omrežje, ena varnost, ena IT izkušnja



ENO omrežje

- Wi-Fi, stikala, security, SD-WAN
- En pogled upravljanja



Predvidljivo delovanje

- Dolg doseg, velika gostota naprav
- Optimizacija aplikacij



Operativna odličnost

- Zagotovljeno delovanje
- Avtomatizacija



Ekonomičnost

- Manj opreme
- Nižji TCO

Več informacij o A1 ICT Distribuciji



| A1 ICT Distribucija

 varnostne-resitve.si

 ict-partners@A1.si





The A1 logo, featuring a red 'A' and a white '1'.

Thank you

Marko Kašić

E marko.kasic@A1.si
M +386 40 440 842